

# Aqua-X Plus System / NFS-3

## Aqua -X Plus Irrigation Control System

The Aqua-X Plus (NFS-3) is a professional-grade multi-zones irrigation control system. It has an 800x480 7" LCD touch-screen monitor, features multiple advanced pump and solenoid control functions, and has greatly expanded device control capacity.



**NFS-3** for Aqua-X Plus Control System

## Connection

### DAISY CHAIN CONNECTION

The sensors and control modules are connected to the NFS-3 with a standard RJ12 cable and RJ12 Y-splitters, making installation as simple as plug-and-play. The modules are "daisy-chained" together using the RJ12 cables allowing for flexible installation, and future expansion. To make installation even easier, you can also use the SPH-1 8-port hub instead of using the Y-splitters.

## Remote Control

### APP-BASED IOS / ANDROID

Besides the onboard user interface / touch-screen, the Trolmaster app will provide real-time data and user notifications from the NFS-3. The NFS-3 also offers a free App TM+ Pro that allows remote control and monitoring through the internet with any smartphone or tablet.

## Specification

### AQUA-X PLUS (NFS-3)

### Dimensions & G.W.

<b>Dimensions</b>	8.66 x 5.79 x 1.06 inch 220 x 147 x 27 mm
<b>Approx. G.W.</b>	0.5kg/ 1.1 lbs

### Operating Requirements

<b>Temperature</b>	32°F to 120°F (0°C to 49°C)
<b>Humidity</b>	5% to 90% RH, non-condensing

### Power Supply


**Supply Voltage** 100-240VAC, 50/60Hz, 3A

### Product Capacity

<b>Sensor Board</b>	Max 5 pcs
<b>Water Detectors (WD-1/2)</b>	Max 20 pcs
<b>Water Content Sensors . (WCS-1/2)</b>	Max 20 pcs
<b>Valves (OA6-24/110, OAT24, DSV-1, DSP-1/2, DSD-1)</b>	Max 10 pcs
<b>Pumps (OA6-24/110, OAT24, DSV-1, DSP-1/2, DSD-1)</b>	Max 10 pcs

### Display & Control

<b>Size</b>	800*480mm (7" LCD Screen)
<b>Control</b>	Touch Screen Control
<b>Language</b>	English (International)
<b>micro-SD</b>	Save/Copy/Import/Export data



## Wiring Diagram

### AQUA-X PLUS (NFS-3)

